We get this new feature with only a few small changes. First, our ConcertChannel needs to add a second broadcast when something is added to the cart:

chapter_09/05/app/channels/concert_channel.rb

```
class ConcertChannel < ApplicationCable::Channel
  def subscribed
    stream_from("concert_#{params[:concertId]}")
  end

  def unsubscribed
    # Any cleanup needed when channel is unsubscribed
  end

  def added_to_cart(data)
    cart = ShoppingCart.find_or_create_by(user_id: data["userId"])
    cart.add_tickets(
      concert_id: data["concertId"],
      row: data["row"],
      seat_number: data["seatNumber"],
      tickets_to_buy_count: data["ticketsToBuyCount"],
      status: data["status"]
    )
    result = Ticket.grouped_for_concert(data["concertId"])
    ActionCable.server.broadcast("concert_#{data["concertId"]}", result)
»   concert = Concert.find(data["concertId"])
»   ActionCable.server.broadcast(
»     "schedule",
»     {
»       concerts: [
»         {
»           concertId: data["concertId"],
»           ticketsRemaining: concert.tickets.unsold.count
»         }
»       ]
»     }
»   )
  end
end
```

Here we have a second broadcast to the schedule channel. The data format is different; it's now an array called concerts, where each element in the array is an object with the properties concertId and ticketsRemaning. In this particular use case,