Using Data Values for Logic

Let's go back to our schedule page. At the top of the page is a run of calendar dates and the Show All button. Earlier, in Chapter 3, *Stimulus*, we added the CssController to make it so that these dates show and hide a red border to indicate which one is active. What we didn't do at the time was wire that state up to allow those dates to act as a filter on the schedule display.

The functionality we want is as follows:

- If none of the date buttons are active, all dates are shown.
- If any of the date buttons are active, only the dates with active buttons are shown.
- The Show All button returns all buttons to the inactive state, making all dates visible.

Two factors make this feature slightly more difficult than the previous Stimulus example. Whether an item displays is dependent on not just the state of that item, but also on the state of the group as a whole. Also, the buttons affect a part of the page that is outside their own subtree of the DOM.

You can manage this in Stimulus in a few different ways. Here's the base HTML for the solution I implemented (it's in the schedule show page, surrounding the calendar header code):

chapter_10/01/app/views/schedules/show.html.erb

```
<div class="grid grid-cols-7 gap-0 mb-6"
   data-controller="calendar">
  <% @schedule.schedule_days.each do |schedule_day| %>
    <% date_string = schedule_day.day.by_example("2006-01-02") %>
    <div class="text-center border-b-2 border-transparent"
       id="calendar-day-<%= schedule_day.day_string %>"
       data-controller="css"
       data-css-css-class="border-red-700"
```