Lower in the view, the “Show All” display is annotated to a different action, cleverly named click->calendar#showAll.

We need to add the expected DOM ID to the schedule day display in app/views/schedule_days/_schedule_day.html.erb:

chapter_10/01/app/views/schedule_days/_schedule_day.html.erb

```
<section id="day-body-<%= schedule_day.day_string %>
  data-controller="css"
  data-css-css-class="hidden"
  data-css-status-value="false">
```

And here’s the Stimulus controller that connects all those pieces (remember to re-run the manifest task):

chapter_10/01/app/javascript/controllers/calendar_controller.ts

```
import { Controller } from "@hotwired/stimulus"

export default class CalendarController extends Controller {
 static targets = ["calendarDay"]
 calendarDayTargets: HTMLElement[]

 everyDayUnselected(): boolean {
  return this.calendarDayTargets.every((target: HTMLElement) => {
   return target.dataset.cssStatusValue === "false"
  })
 }

 filter(): void {
  const everyDayUnselected = this.everyDayUnselected()
  this.calendarDayTargets.forEach((target: HTMLElement) => {
   const show =
    everyDayUnselected || target.dataset.cssStatusValue === "true"
   const schedule = document.getElementById(target.dataset.scheduleId)
   schedule.classList.toggle("hidden", !show)
  })
 }

 showAll(): void {
  this.calendarDayTargets.forEach((target: HTMLElement) => {
   target.dataset.cssStatusValue = "false"
```