```
<%= turbo_frame_tag(
    dom_id(concert),
    class: "concert",
    "data-sort-target": "sortElement",
    "data-sort-value": concert.start_time.to_i,
    "data-#{concert.start_time.by_example("2006-01-02")}": true
  ) do %>
```

Here we added a data-sort-target="sortElement" to make this visible to the SortController and a data-sort-value with the concert start time so the SortController has a value to use. We also added a DOM class, concert, and a dynamic data attribute. The dynamic data attribute is data-#{concert.start_time.by_example("2006-01-02")}, which means it will look like data-2021-02-15=true. These attributes will be used by our new CSS.

At this point, the sorting works. But we don't have headers on each of the dates. This is where our CSS comes in.

Without going into a full CSS reference, a few useful features of CSS will help us out here:

- The ::before selector allows us to insert content before a matching element.
- The [attribute] selector syntax allows us to match CSS on the existence of a specific attribute in an element.
- The first-child selector allows us to limit matches to elements that are the first child of our parent.
- The :not selector allows us to match elements that don't have a particular attribute.
- The + selector allows us to match on an element based on its previous sibling element.

All of these are enough to give us the CSS we need with one additional complication: because all of our text and data attribute names are based on the date of the concert, we only know them at run time, so we need to generate the CSS dynamically using ERB as part of the view file. I told you this was out