there…

This is, to be fair, probably not recommended as a general thing to do, but again, it's here as an example of what you can do with CSS and minimal JavaScript.

There's one HTML change you need in the /schedules/show.html.erb file; the line of code that was data-schedule-id="day-body-<%= schedule_day.day_string %>", now needs to be data-schedule-attribute="data-<%= schedule_day.day_string %>". This is needed to match the new CSS.

Here's what I did. The following code is placed at the top of the show file for schedules, though I think it might be more proper to put it in a Rails content_for block so it could be in the HTML header. This works, though:

chapter_10/04/app/views/schedules/show.html.erb

```
<style>
  <% @schedule.schedule_days.each do |schedule_day| %>
    <% today = "data-#{schedule_day.day.by_example("2006-01-02")}" %>
    .concert[<%= today %>]:first-child::before,
    .concert:not([<%= today %>]) + [<%= today %>]::before
    {
       content: "<%= schedule_day.day.by_example("Monday, January 2, 2006") %>";
       font-size: 1.875rem;
       line-height: 2.25rem;
       font-weight: 700;
    }
  <% end %>
</style>
```

What this code is doing is looping through the list of days and dynamically generating a CSS selector for each day. Here's what one path through the loop might look like:

```
.concert[data-2022-04-28]:first-child::before,
.concert:not([data-2022-04-28]) + [data-2022-04-28]::before
{
  content: "Thursday, April 28, 2022";
  font-size: 1.875rem;
  line-height: 2.25rem;
  font-weight: 700;
```