```
}
```

Translating this from CSS into English, we have a set of styles that describe a big, bold font and the date as our content. This is our header text.

These styles match two separate conditions separated by a comma, both of which specify `::before`, which means the header text will go before a matched element. The first condition is any element that has a CSS class of `concert`, a data-attribute of `data-2022-04-28`, and is the first child of its parent. This catches the first concert in our list and puts a header in front of it.

The second condition is more complicated. It matches an element if the element has a dynamic data-attribute, such as `data-2022-04-28`, and its previous sibling element does not. In other words, it catches boundaries between days, and inserts a header before the first element of any new day. Therefore, if we have two elements in a row, the first with `data-2022-04-27` and the second with `data-2022-04-28`, this selector will match the second element.

This works. Mostly. If you change the time or date of a concert, the Stimulus controller will re-sort it, and the CSS selectors will automatically put the headers in the correct places.

Now, for our calendar filters at the top to still work, we need to make a small change because the headers that they were making visible or invisible no longer exist:

chapter_10/04/app/javascript/controllers/calendar_controller.ts

```
import { Controller } from "@hotwired/stimulus"

export default class CalendarController extends Controller {
  static targets = ["calendarDay"]
  calendarDayTargets: HTMLElement[]

  everyDayUnselected(): boolean {
    return this.calendarDayTargets.every((target: HTMLElement) => {
      return target.dataset.cssStatusValue === "false"
    })
  }
```