```
  filter(): void {
    const everyDayUnselected = this.everyDayUnselected()
    this.calendarDayTargets.forEach((target: HTMLElement) => {
      const show =
        everyDayUnselected || target.dataset.cssStatusValue === "true"
      this.toggleAssociatedConcerts(target.dataset.scheduleAttribute, !show)
    })
  }

  showAll(): void {
    this.calendarDayTargets.forEach((target: HTMLElement) => {
      target.dataset.cssStatusValue = "false"
      this.toggleAssociatedConcerts(target.dataset.scheduleAttribute, false)
    })
  }

  toggleAssociatedConcerts(
    attributeName: string,
    toggleValue: boolean
  ): void {
    document
      .querySelectorAll(`.concert[${attributeName}]`)
      .forEach((element) => {
        element.classList.toggle("hidden", toggleValue)
      })
  }
}
```

All this does is have both the `filter` and `showAll` methods defer to a `toggleAssociatedConcerts` method that looks for all the matching concerts and makes them visible or invisible as required. The CSS headers will update automatically to match.

But there's one problem here. This CSS will only work as written if you change the concert date to one of the already existing dates. Changing to a date outside the list of CSS-generated dates will not match any of the selectors and you won't get a date header. There are a few ways around this problem (limiting the set of dates or generating more CSS, for example), though I suspect a full generic solution would require more custom JavaScript.