run rails kredis:install, which gives us a file at config/redis/shared.yml:

chapter_10/05/config/redis/shared.yml

```
production: &production
  url: <%= ENV.fetch("REDIS_URL", "redis://127.0.0.1:6379/0") %>
  timeout: 1

development: &development
  url: <%= ENV.fetch("REDIS_URL", "redis://127.0.0.1:6379/0") %>
  timeout: 1

  # You can also specify host, port, and db instead of url
  # host: <%= ENV.fetch("REDIS_SHARED_HOST", "127.0.0.1") %>
  # port: <%= ENV.fetch("REDIS_SHARED_PORT", "6379") %>
  # db: <%= ENV.fetch("REDIS_SHARED_DB", "11") %>

test:
  <<: *development
```

All this does is specify the URL for our Redis instance in each environment. We're using the default setup already in our bin/dev so this is fine and we're not going to touch it.

Now that Kredis is installed we have to do three things:

- We need to declare an attribute.
- We need to update that attribute when things happen.
- We need to use that attribute to change the way the page is drawn.

Kredis can work both standalone and integrated with ActiveModel. Standalone, it gives you an object-oriented interface to Redis, allowing you to declare Redis-backed objects. There are a variety of types to choose from, corresponding to data types available in Redis.

```
name = Kredis.string("a_name")
name.value = "Zot"
if name.value == "Zot"
  p "it's a match"
end
```