many pieces of information from the context—the number of seats in a row, the number of tickets to buy, and the list of currently held tickets. Ultimately they return the same list of statuses as the previous version, which are then converted to the correct background color as before.

One important change is that the onSeatChange function no longer calls handlers back up the component tree; instead it just dispatches an action to the context.dispatch method, which changes the context state and triggers redraws as needed across the context provider. Clicking on a seat will cause the appropriate seats to be purchased; other seats to the left will become invalid, and they will also change color.

Subtotal

Our new Subtotal component is where the deleted HTML wound up:

chapter_11/01/app/javascript/components/subtotal.tsx

```
import * as React from "react"
import styled from "styled-components"
import { IsVenueContext, VenueContext } from "./app"

const Header = styled.div`
  font-size: 1.5rem;
  font-weight: bold;
  margin-left: 15px;
  margin-right: 15px;
`


const buttonClass =
  "px-5 py-4 m-2 my-4 w-40 text-center text-white transition-colors " +
  "duration-150 bg-gray-800 rounded-lg focus:shadow-outline hover:bg-black"

const Subtotal = (): React.ReactElement => {
  const context = React.useContext<IsVenueContext>(VenueContext)

  const onClear = () => {
    context.dispatch({ type: "clearHolds" })
  }

  return (
```