```
  "private": "true",
  "dependencies": {
    "@hotwired/stimulus": "^3.0.1",
    "@hotwired/turbo-rails": "^7.1.1",
    "autoprefixer": "^10.4.4",
    "esbuild": "^0.14.36",
    "postcss": "^8.4.12",
    "tailwindcss": "^3.0.24"
  },
  "scripts": {
    "build": "esbuild app/javascript/*.* --bundle
      --sourcemap --outdir=app/assets/builds",
    "build:css": "tailwindcss -i
      ./app/assets/stylesheets/application.tailwind.css
      -o ./app/assets/builds/application.css"
  }
}
```

The package.json file has similar information to the Gemfile, but in JSON format. The important part of the file for us right now is the dependencies part, which lists all the packages our run-time code depends on. Right now we have the two Hotwire libraries, @hotwired/stimulus and @hotwired/turbo-rails, we have three libraries used for CSS processing, tailwindcss, postcss, and autoprefixer, and then esbuild itself.

Later, we'll add a devDependencies section, which has all of the dependencies we use in development and not during run time. This will have our setup for ESlint and Prettier, which are our JavaScript linters, plus eventually our Cypress testing tool.

At the bottom, there's a scripts section, which contains shortcut names for scripts that we can invoke with Yarn. We have two scripts, a build script that triggers esbuild to look at any file in app/javascript/*.* and bundle them all to app/asset/builds, and a build:css script that calls Tailwind on the CSS manifest at application.tailwind.css and outputs that file to application.css. We can invoke these scripts with yarn build and yarn build:css.

Rails also creates a yarn.lock file, which is the equivalent of Gemfile.lock, but *way* more verbose. It has the versions of all our dependencies, and all our dependencies' dependencies, and so on. Part of the complexity is that, unlike