- Any Ruby file in app/helpers that might add CSS classes in helper methods used to build up HTML
- Any JavaScript file in app/javascript that similarly might add or remove CSS classes from our HTML
- The simple form config file in config/initializers declares some CSS classes for form purposes.

We may have a few more entries to add here as time goes on. Note that you don't have to add the main tailwind.css file and you also don't have to add any CSS files being passed to the client directly, the file list here is only for files that are using CSS so that Tailwind can generate the list of needed classes.

The Tailwind starter file is application.tailwind.css:

chapter_01/02/app/assets/stylesheets/application.tailwind.css

```
@tailwind base;
@tailwind components;
@tailwind utilities;
```

All it does is initialize basic Tailwind classes.

Our initial JavaScript is pretty basic, and lives in app/javascript/application.js:

chapter_01/02/app/javascript/application.js

```
import "@hotwired/turbo-rails"
import "./controllers"
```

This imports Turbo and also ./controllers, which will install Stimulus. In the past, standard Rails front-end behavior, like alert messages or HTTP methods on forms, was handled by a separate library called Rails UJS (Unobtrusive JavaScript). Those functions are now handled by Turbo.

I'll talk more about the Stimulus setup in Chapter 3, *Stimulus*, but for now I'll just say that the import initializes Stimulus and loads any Stimulus code we