Writing the First Test

Delete the cypress/integration/examples directory with all the existing Cypress tests. Then, restart Cypress with rake cypress:open. This gives us the Cypress window with a message saying we have no tests. (Or it might re-create the same sample tests, in which case just delete them again, write the next test, and then open Cypress.) Let's write the first line of a new test. Create a file named cypress/schedule/schedule_spec.js. As soon as you save it, the Cypress window changes to show that file. If you start to "Run all specs," you get the test runner with a message that no tests are found in the file.

Now let's start writing the test:

chapter_14/02/cypress/integration/schedule/schedule_spec.js

```
describe("On the schedule page", function () {
  beforeEach(function () {
    cy.request("/cypress_rails_reset_state")
  })

  it("Visits our schedule page ", function () {
    cy.visit("/")
  })
})
```

Note: This is in JavaScript, not TypeScript, because it's going to make very little difference in writing tests, and also the TypeScript setup for Cypress is a bit of a pain.

The test syntax here is similar to the Jasmine or Jest JavaScript tools. A describe method defines a series of tests, while the it method describes an individual test. Both of those methods take a string argument that is a name and a function argument that is the actual test or set of tests being defined.

Looking at the top of this test file, you will see we have included a beforeEach block, which is evaluated before every test in the describe block. Our beforeEach makes a special call to a route defined by the cypress-rails gem called