```
cy.request(url).should((response) => {
  expect(response).to // something
}
```

Cypress also has commands for interacting with cookies and local storage, and a `go` command that allows you to interact with the browser web history, `cy.go("back")`.

Finders

Once you've visited a site and set up DOM elements, you probably want to search them for specific elements. Cypress provides a lot of find and search methods that are heavily influenced by jQuery, which is to say that the methods typically take a selector and yield a Cypress object that contains a list of DOM elements that match the selector. The selector syntax is the same as jQuery's: `.` indicates a DOM class, `#` is a DOM ID, and an `[attribute=value]` matches a DOM attribute. If you are concerned about selectors changing in your code due to design changes, Cypress recommends fixing elements by setting a `data-cy` attribute on them and then querying with something like `cy.get("[data-cy=myelementidentifier]")`.

Only a few of these finder commands actually are callable directly on the `cy` object, like `cy.get(".thing")`. Most of them chain off the result of the `get`, as in `cy.get(".thing").first()`. Most of the time, you will start with `cy.get()`. Alternately, you can start with `cy.contains("Text")`, which searches for a DOM element containing the given text or matching a given regular expression.

Once you have a set of DOM elements via `get` or `contains`, you can traverse the DOM tree in several ways. You can continue to search with your DOM elements with `find`, which filters on another selector, `cy.get(".thing").find(".other")`, and yields elements with DOM class `other` that are inside elements with DOM class `thing`. A series of other commands allow you to traverse the tree, like `children`, `parents`, and so on, but they are less common. You can get a specific element from a list with `first`, `last`, or `eq(index)`. The index in `eq` either starts with `0` to get the first element and goes up to move forward, or with `-1` to get the last element and goes down to move backward.

If the result of these find commands is empty, all of these find commands will