```
}

export default Seat
```

Here we're adding a data-cy that will be of the form 1x5 and will allow us to identify the row and seat number of an element in one attribute. We're also adding a data-color, which is the color that the styled component will also be using as the background color of the class. This is not ideal, and I think that if I were starting over, I would probably find something other than styled-components, but it's workable and we can write tests against it, like so:

chapter_15/02/cypress/integration/concert/concert_spec.js

```
describe("On a concert page", () => {
  beforeEach(function () {
    cy.request("/cypress_rails_reset_state")
    cy.request("POST", "/test/log_in_user")
    cy.visit("/concerts/last")
  })

  it("blocks tickets on edge when ticket list changes", () => {
    cy.get("[data-cy=1x10]").should("have.attr", "data-color", "white")
    cy.get("[data-cy=ticketsToBuy]").select("3")
    cy.get("[data-cy=1x10]").should("have.attr", "data-color", "yellow")
    cy.get("[data-cy=1x9]").should("have.attr", "data-color", "yellow")
    cy.get("[data-cy=1x8]").should("have.attr", "data-color", "white")
  })

  it("marks a ticket as sold on click", () => {
    cy.get("[data-cy=1x10]").click()
    cy.get("[data-cy=1x10]").should("have.attr", "data-color", "green")
    cy.get("[data-cy=1x9]").should("have.attr", "data-color", "white")
    cy.get("[data-cy=ticketsPurchased").should("have.text", "1")
    cy.get("[data-cy=ticketCost").should("have.text", "$15.00")
  })

  it("marks a group of tickets sold on click", () => {
    cy.get("[data-cy=ticketsToBuy]").select("2")
    cy.get("[data-cy=1x9]").click()
    cy.get("[data-cy=1x9]").should("have.attr", "data-color", "green")
    cy.get("[data-cy=1x10]").should("have.attr", "data-color", "green")
    cy.get("[data-cy=1x8]").should("have.attr", "data-color", "yellow")
    cy.get("[data-cy=ticketsPurchased").should("have.text", "2")
```