```
  gem install foreman
fi

foreman start -f Procfile.dev
```

All this does is install Foreman if not installed, and then uses it to start up the Procfile.dev.

When you run it, you'll get something like this:

```
$ bin/dev
14:36:31 web.1  | started with pid 985
14:36:31 js.1   | started with pid 986
14:36:31 css.1  | started with pid 987
14:36:32 js.1   | yarn run v1.22.17
14:36:32 css.1  | yarn run v1.22.17
14:36:32 js.1   | $ esbuild app/javascript/*.* --\
  bundle --sourcemap --outdir=app/assets/builds
  --watch 14:36:32 css.1  | $ tailwindcss -i
  ./app/assets/stylesheets/application.tailwind.css -o
  ./app/assets/builds/application.css --watch
14:36:32 web.1  | => Booting Puma
14:36:32 web.1  | => Rails 7.0.0 application starting in development
14:36:32 web.1  | => Run `bin/rails server --help` for more startup options
14:36:32 js.1   | [watch] build finished, watching for changes...
14:36:32 web.1  | Puma starting in single mode...
14:36:32 web.1  | * Puma version: 5.5.2 (ruby 3.0.3-p157) ("Zawgyi")
14:36:32 web.1  | *  Min threads: 5
14:36:32 web.1  | *  Max threads: 5
14:36:32 web.1  | *  Environment: development
14:36:32 web.1  | *          PID: 985
14:36:32 web.1  | * Listening on http://127.0.0.1:3000
14:36:32 web.1  | * Listening on http://[::1]:3000
14:36:32 web.1  | Use Ctrl-C to stop
14:36:32 css.1  |
14:36:32 css.1  | Rebuilding...
14:36:32 css.1  | Done in 68ms.
```

All three processes start. Log entries from each process are timestamped and marked with the name of the process that logged them, which is handy.

The js process runs esbuild, then says it's done and is still watching for changes. The css process runs Tailwind and reports that it's time to run. The web process