The final line pins all the files in the app/javascript/controllers, allowing them to be individually referenced as imports as controllers/<whatever>.

The Stimulus import file has also changed:

appendix_hotwire/01/app/javascript/controllers/index.js

```
// Import and register all your controllers from the importmap
// under controllers/*

import { application } from "controllers/application"

// Eager load all controllers defined in the import map under
// controllers/**/*_controller
import { eagerLoadControllersFrom } from "@hotwired/stimulus-loading"
eagerLoadControllersFrom("controllers", application)

// Lazy load controllers as they appear in the DOM
// (remember not to preload controllers in import map!)
// import { lazyLoadControllersFrom } from "@hotwired/stimulus-loading"
// lazyLoadControllersFrom("controllers", application)
```

It still imports the application.js file in that directory that specifies debug and other parameters, but now, rather than have a manifest, it just calls eagerLoadControllersFrom, which causes all the underlying controllers to be loaded. In conjunction with the pin_all_from command, this will put all the controllers in the import map going to the browser.

If you would prefer to lazy load only the controllers that are used on a given page, the comments show how to do that.

When sent to the browser by the <%= javascript_importmap_tags %> command in the header of the layout file, the result looks like this, where I've replaced the long digest fingerprints with the word DIGEST to keep the lines visible:

```
<script type="importmap" data-turbo-track="reload">{
  "imports": {
    "application":
       "/assets/application-DIGEST.js",
    "@hotwired/turbo-rails":
```