The All-Hotwire App

These were the list of features in the venue page that I wanted to replicate in Hotwire:

- Unroll the markup from the React components and go back to an ERB template.
- Add the interaction for changing the number of tickets to buy, which also changes the status of seats from valid to invalid and vice versa. This includes talking to the server.
- Add the interaction for clicking on a seat, which updates the status of that seat, the seats to its left and right (which might be purchased or become invalid), and the subtotal. This also includes talking to the server.
- Add the interaction for the Clear All button.
- Add ActionCable functionality for communicating between multiple browsers.

I had a couple of design decisions to make. My goal here was to make this app as Hotwire-forward as I could, meaning state and logic on the server to the extent possible. (*Note:* If you had a beta version of the first edition of this book, this is a significantly different design for the Stimulus version of the app.) It seemed to me as I started that both the ticket-to-buy and the seat button press could be modeled as HTTP form requests with Turbo Stream responses.

The piece that looks tricky is the last one where browsers are communicating ticket purchases. The reason I think this might be complicated is that it's the one place where the client-side state actually matters. As currently written, the server can't correctly send the new state of the client as pure HTML to all browsers because the other browsers might have a different "Tickets to Buy" set, and therefore would send different HTML based on a client-side value that the server doesn't know about.