```
    <span>Current Tickets Purchased:  </span>
    <span data-cy="ticketsPurchased">
      <%= Ticket.user_for_concert(concert.id, user&.id).count %>
    </span>
  </div>
  <div class="text-2xl font-bold mx-4">
    <span>Current Tickets Cost:  </span>
    <span data-cy="ticketCost">
      <%= Ticket.user_for_concert(concert.id, user&.id).count * 15 %>.00
    </span>
  </div>
  <div class="<%= SimpleForm.button_class %> w-48 font-bold"
    data-cy="clearButton"
    data-controller="clear-all"
    data-clear-all-hidden-id-value="tickets_to_buy_count"
    data-action="click->clear-all#submit">
    <%= form_with(
        url: clear_all_tickets_url,
        method: "delete",
        data: {"clear-all-target": "form"}
      ) do |f| %>
      <%= hidden_field_tag(:concert_id, concert.id) %>
      <%= hidden_field_tag(
          "tickets_to_buy_count",
          "",
          id: "clear_all_tickets_count",
          data: {"clear-all-target": "hiddenField"}
        ) %>
      Clear Tickets
    <% end %>
  </div>
 </section>
<% end %>
```

The venue header is a little more interesting, as we define two Stimulus controllers, both of which take the form as a target:

appendix_hotwire/01/app/views/venues/_venue_header.html.erb

```
<section class="venue-header">
  <div>
    <div class="flex text-2xl font-bold mx-4">
      <span>How many tickets would you like?</span>
```