```
      <span class="select ml-4"
          data-controller="form cable-receiver"
          data-cable-reciever-channel-name-value="ConcertChannel"
          data-cable-receiver-concert-id-value="<%= concert.id %>">
        <%= form_with(
            url: tickets_to_buy_count_path,
            method: "patch",
            data: {
              "form-target": "form",
              "cable-receiver-target": "form"
            }
          ) do |f| %>
          <%= hidden_field_tag(:concert_id, concert.id) %>
          <%= hidden_field_tag(:venue_id, venue.id) %>
          <%= select_tag(
              :tickets_to_buy_count,
              options_for_select(1..venue.seats_per_row),
              "data-cy": "ticketsToBuy",
              "data-action": "change->form#submit"
            ) %>
        <% end %>
      </span>
    </div>
  </div>
</section>
```

The select box also triggers a Stimulus action when it changes, and we'll see what that action does in a moment.

The venue body loops over rows in much the same way that the React code did:

appendix_hotwire/01/app/views/venues/_venue_body.html.erb

```
<section class="venue-body">
  <%= turbo_frame_tag("venue-body") do %>
    <table className="table">
      <tbody>
        <% concert.rows(
            tickets_to_buy_count: tickets_to_buy_count).each do |row| %>
          <%= render(row, user: user, concert: concert) %>
        <% end %>
      </tbody>
    </table>
  <% end %>
```