```
</section>
```

I've made Row and Seat both Rails ActiveModels, which means even though they don't specifically map to the database, we can use Rails naming conventions on them. For our purposes right now, that means rendering a row object invokes a file at app/views/rows/_row.html.erb:

appendix_hotwire/01/app/views/rows/_row.html.erb

```
<tr class="h-20" id="<%= dom_id(row) %>">
  <% row.seats.each do |seat| %>
    <%= render(seat, user: user, row: row, concert: concert) %>
  <% end %>
</tr>
```

Which, in turn, loops over seats that have partials at app/views/seats/_seat.html.erb:

appendix_hotwire/01/app/views/seats/_seat.html.erb

```
<td>
  <span
    class="p-4 m-2 my-10 text-lg
          transition-all duration-1000 ease-in-out
          <%= seat.hover_color_for(user) %>
          border-black border-4 <%= seat.color_for(user) %>"
    data-cy="<%= seat.row_seat %>"
    data-color="<%= seat.color_for(user) %>"
    data-status="<%= seat.status(user) %>">
    <% if seat.status(user) == "unsold" || seat.status(user) == "held" %>
      <%= button_to(
          seat.number,
          seat_path(
            id: seat.id,
            user_id: user.id,
            row_number: row.number,
            seat_number: seat.number,
            tickets_to_buy_count: row.tickets_to_buy_count,
            concert_id: concert.id
          ),
          method: seat.status(user) == "unsold" ? "put" : "delete",
          form: {class: "inline"},
          class: "bg-white"
        ) %>
```