The form submission goes to a new controller with a new resource called tickets_to_buy, which we need to declare in the Rails routes file:

appendix_hotwire/01/config/routes.rb

```
resource(:tickets_to_buy_count, only: :update)
resource(:clear_all_tickets, only: :destroy)
resources(:seats, only: %i[update destroy])
```

This gives us tickets_to_buy as a Rails singular resource, meaning we can call the update route without needing an ID for a resource being updated. This is perfect for us, because this resource is effectively common for this page.

We're not actually saving the ticket-to-buy number server side; we're just using it to trigger a redraw. Here's the controller:

appendix_hotwire/01/app/controllers/tickets_to_buy_counts_controller.rb

```
class TicketsToBuyCountsController < ApplicationController
 def update
  @venue = Venue.find(params[:venue_id])
  @concert = Concert.find(params[:concert_id])
  @user = current_user
 end
end
```

The controller just does the default action of finding a turbo_stream view:

appendix_hotwire/01/app/views/tickets_to_buy_counts/update.turbo_stream.erb

```
<%= turbo_stream.replace(
    "venue-body",
    partial: "venues/venue_body",
    locals: {
      concert: @concert,
      user: @user,
      tickets_to_buy_count: params[:tickets_to_buy_count].to_i
    }
  ) %>
<%= turbo_stream.replace(
    "subtotal",
    partial: "venues/subtotal",
```