```
    locals: {concert: @concert, user: @user}
  ) %>
```

The view does two Turbo Stream replace actions. One of them is to the venue_body redrawing the partial for the entire grid with the new value for tickets to buy. This causes a new grid of seats to be set server side with new validation calculations and replaces the existing grid of seats. The other Turbo Stream replace updates the subtotal display. We don't actually need it here, but it's going to be helpful for the ActionCable updates.

The other user interaction here comes from clicking on a seat—we've used button_to to make those buttons into individual form submissions, going to a Seat controller. The controller is more complicated than the ticket-to-buy one because it needs to manage saving the new ticket holds and also broadcast those changes via ActionCable. Essentially, it has the exact logic that the last React version was doing via ActionCable uploads in the ConcertChannel:

appendix_hotwire/01/app/controllers/seats_controller.rb

```
class SeatsController < ApplicationController
  before_action :load_data, only: [:update, :destroy]

  def update
    @cart.add_tickets(
      concert_id: params[:concert_id].to_i,
      row: params[:row_number].to_i,
      seat_number: params[:seat_number].to_i,
      tickets_to_buy_count: params[:tickets_to_buy_count].to_i,
      status: "held"
    )
    load_row
    @concert.broadcast_schedule_change
  end

  def destroy
    @cart.clear(
      concert_id: params[:concert_id],
      row: params[:row_number].to_i,
      seat_number: params[:seat_number].to_i,
      tickets_to_buy_count: params[:tickets_to_buy_count].to_i,
      status: "unsold"
```