```
  static values = { hiddenId: String }

  submit() {
    const hiddenValueElement = document.getElementById(this.hiddenIdValue)
    if (hiddenValueElement) {
      this.hiddenFieldTarget.value = hiddenValueElement.value
    }
    this.formTarget.requestSubmit()
  }
}
```

There's probably a more generic version of this that I could write if I needed it again.

The form submits to a controller that is very similar to the Seat controller, but we'll give it its own REST action:

appendix_hotwire/01/app/controllers/clear_all_tickets_controller.rb

```
class ClearAllTicketsController < ApplicationController
  def destroy
    @cart = ShoppingCart.find_or_create_by(user_id: params[:user_id])
    @concert = Concert.find(params[:concert_id])
    @user = current_user
    @cart.clear_all(concert_id: @concert.id, user_id: @user.id)
    @concert.broadcast_schedule_change
  end
end
```

We'll also give it a Turbo Stream view that redraws the venue:

appendix_hotwire/01/app/views/clear_all_tickets/destroy.turbo_stream.erb

```
<%= turbo_stream.replace(
      "venue-body",
      partial: "venues/venue_body",
      locals: {
        concert: @concert,
        user: @user,
        tickets_to_buy_count: params[:tickets_to_buy_count].to_i
      }
    ) %>
```