- There's some minor date parsing and formatting on this page. Rather than introduce a new JavaScript library to manage this, I did it on the server side and had the formatted and parsed data made part of the data sent to React.

- I decided to keep the show/hide behavior via CSS classes, even though React makes it relatively easy to just remove and reinsert the DOM elements. This was to keep from also having to rewrite the tests, and also to avoid more complicated conditional logic in the React components.

We have to roll the markup up into React components and then make those components talk to and receive data from the reducers. Let's start on the Rails side.

The controller changes slightly to allow for a JSON call:

appendix_react/01/app/controllers/schedules_controller.rb

```
class SchedulesController < ApplicationController
 def show
  @concerts = Concert.includes(:venue, gigs: :band).all
  @schedule = Schedule.from_concerts(@concerts)
  @schedule.hide(params[:hidden]&.split(",") || [])
  @schedule.schedule_day_at(params[:toggle])&.toggle!
  favorites = current_user&.favorites || []
  respond_to do |format|
   format.html
   format.json do
    render(
     json: {
      scheduleDays: @schedule.days_hash,
      favorites: favorites.map { |f| f.concert.to_h },
      userId: current_user.id
     }
    )
   end
  end
 end
end
```

The JSON calls some mostly boilerplate methods on Schedule, ScheduleDay, and Concert that I'm not going to show. For right now it's enough to say they prepare