Fetching React Data

Let’s first start by looking at how the data comes in. Here’s the top-level schedule app, again with some setup elided:

appendix_react/01/app/javascript/components/schedule/schedule_app.tsx

```
export const ScheduleApp = ({
  favoriteChannelName,
}: ScheduleAppProps): React.ReactElement => {
  const store = scheduleStore
  store.dispatch({ type: "initEmpty" })
  initScheduleChannel()
  initFavoritesChannel(favoriteChannelName)
  store.dispatch(fetchData())
  return (
    <Provider store={store}>
      <section>
        <ScheduleFilter />
        <ScheduleFavorites />
        <ScheduleDisplay />
      </section>
    </Provider>
  )
}
```

We grab the scheduleStore, which is created in our new context file for this app:

appendix_react/01/app/javascript/contexts/schedule_context.ts

```
export const scheduleStore = configureStore({ reducer: scheduleReducer })
export type RootState = ReturnType<typeof scheduleStore.getState>
export type AppDispatch = typeof scheduleStore.dispatch

export const useAppDispatch = () => useDispatch<AppDispatch>()
export const useAppSelector: TypedUseSelectorHook<RootState> = useSelector
```

The schedule store has an initial state, and again, there’s some boilerplate in setting up the reducer that I’m not showing right here as it’s very similar to the last reducer.

Here’s the initial state: