```
  "compilerOptions": {
    "declaration": false,
    "emitDecoratorMetadata": true,
    "experimentalDecorators": true,
    "lib": ["es2019", "dom"],
    "jsx": "react",
    "module": "es6",
    "moduleResolution": "node",
    "baseUrl": ".",
    "paths": {
      "*": ["node_modules/*", "app/packs/*"]
    },
    "sourceMap": true,
    "target": "es2019",
    "noEmit": true
  },
  "exclude": ["**/*.spec.ts", "node_modules", "vendor", "public"],
  "compileOnSave": false
}
```

I'll talk about what all this means in Chapter 6, *TypeScript*.

Right now we need to update our dev scripts to use tsc-watch.

The new scripts look like this—remember you can't have line breaks in the actual JSON file:

```
"scripts": {
  "build:js":
    "esbuild app/javascript/*.* --bundle
      --sourcemap --outdir=app/assets/builds",
    "build:css":
      "tailwindcss -i ./app/assets/stylesheets/application.tailwind.css -o
      ./app/assets/builds/application.css",
    "failure:js":
      "rm ./app/assets/builds/application.js &&
       rm ./app/assets/builds/application.js.map",
    "dev":
      "tsc-watch --noClear -p tsconfig.json
       --onSuccess \"yarn build:js\"
       --onFailure \"yarn failure:js\""
}
```