A couple of things to note here. One is that I forgot that we also have a Show/Hide toggle button on the favorites list itself, which is managed here via a button that toggles a value in the reducer. The image is a special case here. Technically, you can import an image file using esbuild, which places it in the app/assets/build/ file and allows you to import it as though it was any other file, in practice, esbuild's attempt to add a fingerprint to the file clashes with Propshaft, so I just moved the image to the public directory and referenced the source name directly.

The thing I really want to point out is how the individual ScheduleFavorite components are called. They have an animateIn property that is true if the concert is the mostRecentFavoriteId and a shouldBeVisible property that's true if the concert is not on the list of removed favorite IDs.

Here's how those properties are used:

appendix_react/01/app/javascript/components/schedule/favorite.tsx

```
import * as React from "react"
import {
  Concert,
  buttonClass,
  removeFavorite,
  useAppDispatch,
} from "../../contexts/schedule_context"

interface SearchResultProps {
  favorite: Concert
  animateIn: boolean
  shouldBeVisible: boolean
}

export const Favorite = ({
  favorite,
  animateIn,
  shouldBeVisible,
}: SearchResultProps): React.ReactElement => {
  const dispatch = useAppDispatch()
  const [animateOut, setAnimateOut] = React.useState(false)
  const [display, setDisplay] = React.useState(shouldBeVisible)
```