table. (If the Turbo Frame tag is only inside a single td, that'll work fine.) The workarounds are to either wrap the entire table or use CSS grids for table behavior.

We can polish this interaction by supporting a Cancel button in the form and also by properly handling submission errors. This is all standard Rails, made just a tiny bit more complicated by the fact that I've set up the application to have two different concert displays: the inline one that we see on the schedule page, and the actual concert show page that you can see at a URL like http://localhost:3000/concerts/58.

To make this work, we need to make two changes to the concert form.

The error display for the form is currently at the bottom of the form, and we want to move that to the top of the form, inside the simple_form_for call, at the top of that block:

chapter_02/02/app/views/concerts/_form.html.erb

```
<% if f.object.errors.present? %>
  <div class="text-red-500 border-red-800 font-bold border-2 p-2 mb-2">
    <%= f.error_notification %>
    <%= f.error_notification(
        message: f.object.errors.full_messages.to_sentence
      ) %>
  </div>
<% end %>
```

If there are errors, Rails will put them in the view inside the div, which will show up with a red outline.

At the end of the form, where the Submit button is, we need to add a cancel link (this can just be a regular anchor tag, since the cancel is just a GET request to go back to the server for a show action):

chapter_02/02/app/views/concerts/_form.html.erb