```
      No favorite concerts yet
    <% end %>
  </div>
  <div id="favorite-concerts-list">
    <% current_user.favorites.each do |favorite| %>
      <%= render(favorite) %>
    <% end %>
  </div>
 </section>
<% end %>
```

While we're at it, let's also create a Favorites index page that just draws the partial:

chapter_02/03/app/views/favorites/index.html.erb

```
<%= render "favorites/list" %>
```

A blank `index` method is added to the controller as well. Just `def index; end` should do it. This will allow us to refer to this in a redirect or as a render helper.

Notice that the call to render the concert inside the list just calls `render(favorite)`. This draws the view partial at `app/views/favorites/_favorite`, which is (slightly) different from the regular concert partial, but will make it easier to distinguish between the favorite display and the concert display later on.

Now, we need to change the behavior of the Favorite and Unfavorite buttons to have the `data-turbo-frame` attribute:

chapter_02/03/app/views/concerts/_concert.html.erb

```
<% if current_user.favorite(concert) %>
  <%= button_to(
      "Unfavorite",
      favorite_path(id: current_user.favorite(concert)),
      method: "delete",
      form: {data: {"turbo-frame": "favorite-concerts"}},
      class: SimpleForm.button_class
    ) %>
<% else %>
  <%= button_to(
      "Favorite",
```