```
<%= turbo_stream.update("no-favorites") do %>
  
<% end %>
```

This code uses a set of helpers defined by turbo-rails and based off of turbo_stream: one helper for each action. The first argument is the target DOM ID for the Turbo Stream, and the remaining arguments are passed through to render. Anything you can do in a controller render you can do here. Alternately, the method can take a block, where the contents of the block are the children of the Turbo Stream, similar to how blocks work in other Rails helpers like form_with, link_to or content_tag.

In this case, we are using the append action to append one favorite view to the favorite-concerts-list. We are passing @favorite to use the default favorite partial view we've already created. Then we are using the replace action to overwrite the existing concert display given its new status as a favorite. Finally, we're taking out the text "No favorite concerts yet", because, by definition, there is now a favorite concert, so we're just passing a blank space to the div that displays that text.

The destroy file is similar:

chapter_02/04/app/views/favorites/destroy.turbo_stream.erb

```
<%= turbo_stream.remove(dom_id(@favorite)) %>
<%= turbo_stream.replace(dom_id(@favorite.concert), @favorite.concert) %>
<% if current_user.favorites.empty? %>
 <%= turbo_stream.update("no-favorites") do %>
  No favorite concerts yet
 <% end %>
<% end %>
```

The second part with the replacement is the same, but we're starting with a remove action to get the favorite version of the display off the page, and finishing by dynamically setting the "No favorite concerts yet" text if the user has no favorites after the removal.

And that, once again, is that. Reload the page and the Make Favorite and