Adding Our First Controller

The first thing we're going to do with Stimulus is make a Show/Hide button that will toggle the contents of the favorite concerts block on our page.

The bulk of your Stimulus code will go into a *controller,* which is similar to your Rails controller in that it's where the responses to events are stored, but different in that there's much less structure and fewer expectations around a Stimulus controller than a Rails controller.

To invoke a controller, we add an attribute named data-controller to a DOM element on your page. The value of the attribute is the name of the controller. If we added an attribute data-controller="toggle", then Stimulus attaches it to a ToggleController, which it expects will be at controllers/toggle_controller.ts (or .js).

If the controller's name is more than one word, you use dash case, so it would be data-controller="fancy-color", not fancyColor. The controller has the same scope as the DOM element it's attached to. This means that any events you want dispatched to the controller need to happen inside the controller's DOM element. Any elements you designate as targets for the controller also need to be inside the controller's DOM element.

In our app we want to have a Show/Hide button, so we want to be able to press the button, hide the list of favorite concerts, and change the text of the button. This means our Stimulus controller needs to be attached to a DOM element that encompasses both the button and all the favorite concerts.

Happily, we have such a DOM element. It's the parent <section> element in our favorites/_list partial. We want to give it a data-controller attribute:

chapter_03/01/app/views/favorites/_list.html.erb

```
<section class="my-4" data-controller="favorite-toggle">
```

Here we are adding the DOM attribute data-controller and giving it the value favorite-