Creating an Action

In Stimulus, an *action* is what connects a DOM event to the controller code that you want executed when that event happens. Like controllers, Stimulus actions are defined using a data attribute in the markup: you add the attribute to the DOM element whose events you want to watch. In our case, we want to add a button that says “Hide”—the new button goes right after the title element that displays “Favorite Controllers”:

chapter_03/02/app/views/favorites/_list.html.erb

```
<div class="text-3xl font-bold">
  Favorite Concerts
  <button
    class="<%= SimpleForm.button_class %> py-1 text-xl font-semibold"
    data-action="click->favorite-toggle#toggle">
    Hide
  </button>
</div>
```

The line that defines the actions is `data-action="click->favorite-toggle#toggle"`. The `data-action` is the attribute name that signals to Stimulus that an action is being defined. The value of the `data-action` attribute is a mini-language to define the connection between the event and the code.

The mini-language, which Stimulus calls an *action descriptor*, has three parts:

- The first element is the name of the event being watched for, which in our case is `click`, followed by an arrow (`->`).
- The second element is the name of the controller, spelled exactly the way the name is spelled where the controller is defined, meaning that it’s dash-case. For us, that’s `favorite-toggle`. This element ends with a hashtag (`#`).
- The last element is the name of the method to be called on the controller when the event happens. This needs to be the exact name of the method, which usually means it’s in camelCase. (I’m not sure why Stimulus chooses