If you want to, you have a limited ability to pass an arbitrary value to the action method. The value doesn't come to the method as a new argument; rather, the exiting event argument has a params attribute that you can populate. To do this, you need to add another data attribute to the DOM element that contains the data-action attribute. The pattern of this element is data-<controller>-<attribute>-param. The resulting event argument to the method then has a params object that features an attribute named the same as the attribute part of the value, so data-controller-flavor-param="sweet" would result in a params object including {flavor: "sweet"}.

Let's do this to specify the message we want to send to the console on click—this is an arbitrary example, because later we're going to use that toggle method to actually toggle something, but right now, let's pass an argument to our FavoriteToggleController and send that along to the console.

The params element in place is a little bit of a mouthful:

chapter_03/03/app/views/favorites/_list.html.erb

```
<div class="text-3xl font-bold">
  Favorite Concerts
  <button
     class="<%= SimpleForm.button_class %> py-1 text-xl font-semibold"
     data-action="click->favorite-toggle#toggle"
     data-favorite-toggle-text-param="Hello from the ERB file!">
    Hide
  </button>
</div>
```

Our argument is named data-favorite-toggle-text-param. The resulting event argument will allow us to recover that value as event.params.text. Or we can destructure the argument and use it directly:

chapter_03/03/app/javascript/controllers/favorite_toggle_controller.ts

```
import { Controller } from "@hotwired/stimulus"

export default class FavoriteToggleController extends Controller {
  toggle({ params: { text } }): void {
    console.log(text)
```