Adding a Target

In client-side coding, it is fairly common to want to mark a particular DOM element as being of interest to the code. Typically this means either you are reading the DOM element's state to determine what to do or you are changing the DOM element's state as a result of some other event. In our case, it's the latter: we want to add the DOM class `hidden` to an element to hide it, and eventually we want to change the text of the button itself.

In a world without a framework, or in jQuery world, we would identify these elements using a DOM ID or DOM class. However, because those DOM attributes are also used to manage CSS styling, it can be confusing as to what DOM ID or class elements are styling and which are used by JavaScript.

Stimulus allows you to explicitly identify DOM elements of interest by marking them as *targets*. A target is identified using a specially named attribute of the format `data-<controller name>-target` attribute on a DOM element. The value of the attribute is the name of the target. Target names need to be in camelCase in the HTML attribute.

Our target element is the element we want to hide. In this case, that's the body of the list, which is currently not its own `div` element. Let's make it so:

chapter_03/04/app/views/favorites/_list.html.erb

```
<div data-favorite-toggle-target="elementToHide">
  <div class="text-xl font-bold" id="no-favorites">
    <% if current_user.favorites.empty? %>
      No favorite concerts yet
    <% end %>
  </div>
  <div id="favorite-concerts-list">
    <% current_user.favorites.each do |favorite| %>
      <%= render(favorite) %>
    <% end %>
  </div>
</div>
```