We've surrounded the display with a `div` element that we have given a target attribute of `data-favorite-toggle-target="elementToHide"`. This attribute declaration sets up the `FavoriteToggle` controller to have a target named `elementToHide`.

That declaration sets up the target on the HTML side, but we also need to declare the target in the controller, and the mechanism is a little different depending on whether you are using TypeScript or JavaScript. Here's the way it works in TypeScript:

chapter_03/04/app/javascript/controllers/favorite_toggle_controller.ts

```
import { Controller } from "@hotwired/stimulus"

export default class FavoriteToggleController extends Controller {
  static targets = ["elementToHide"]
  elementToHideTarget: HTMLElement

  toggle(): void {
    this.elementToHideTarget.classList.toggle("hidden")
  }
}
```

Stimulus requires that any targets in use from the controller need to be declared in a static variable called `targets`, as in our line `static targets = ["elementToHide"]`. Once that declaration is in place, Stimulus defines three properties on the controller you can use:

- `<targetName>Target` (as in `elementToHideTarget`): This property returns the first DOM element in the scope of the controller that declares this target. If there is no such element, accessing the property raises an exception.

- `<targetName>Targets` (as in `elementToHideTargets`): This property returns an array of all the DOM elements in the scope of the controller that declare this target.

- `has<targetName>Target` (as in `hasElementToHideTarget`): This property returns a boolean value—true if there is a `elementToHideTarget`, false otherwise. You'd typically use this method to avoid the exception raised by `elementToHideTarget`.