later examples, we show user input in a bold font.) The ^D is the end-of-file character on Unix systems.

```
$ ruby copy.rb
These are lines
These are lines
that I am typing
that I am typing
^D
```

We can also pass in one or more filenames on the command line, in which case the filenames are passed to standard input and the Kernel#gets will read from each in turn as if all the files in the command line were concatenated to a single file. From the top directory of the sample code:

```
$ ruby code/tut_io/copy.rb testfile
This is line one
This is line two
This is line three
And so on...
```

We have another option.

we can explicitly open the file and read from it using File#gets:

```
File.open("testfile") do |file|
  while line = (file.gets)
    puts line
  end
end
```

produces:

```
This is line one
This is line two
This is line three
And so on...
```

In addition to gets, I/O objects define an additional set of access methods, all intended to make our lives easier.

Iterators for Reading

While the usual loops work to allow you to read data from an IO stream, Ruby also defines some task-specific iterators. The method each_byte invokes a block with the next 8-bit byte from an IO object (in this case, an object of type File). The Integer#chr method converts an integer to the corresponding ASCII character:

```
File.open("testfile") do |file|
  file.each_byte.with_index do |ch, index|
    print "#{ch.chr}:#{ch} "
    break if index > 10
  end
end
```

produces:

```
T:84 h:104 i:105 s:115  :32 i:105 s:115  :32 l:108 i:105 n:110 e:101
```