```
    assert_raises(RuntimeError) { Roman.new(5000) }
  end
end
```

produces:

```
Run options: --seed 42163
# Running:

..
Finished in 0.000432s, 4629.6296 runs/s, 16203.7037 assertions/s.
2 runs, 7 assertions, 0 failures, 0 errors, 0 skips
```

We could do more testing on our Roman class, but let's move on. We've only scratched the surface of the set of assertions available inside the testing framework. For example, for every positive assertion, such as assert_equal, there's a negative refutation (in this case refute_equal).

The final parameter to every assertion is an optional message that will be output before any failure message. This normally isn't needed, because the failure messages are normally pretty reasonable. The one exception is the assertion refute_nil, where the default message "Expected nil to not be nil" doesn't help much. In that case, you may want to add some annotation of your own. (This code assumes the existence of some kind of User class.)

```
require 'minitest/autorun'
class ATestThatFails < Minitest::Test
 def test_user_created
   user = User.find(1)
   refute_nil(user, "User with ID=1 should exist")
 end
end
```

produces:

```
Run options: --seed 47419
# Running:

F
Failure:
ATestThatFails#test_user_created [prog.rb:11]:
User with ID=1 should exist.
Expected nil to not be nil.

rails test tmp/prog.rb:9


Finished in 0.000535s, 1869.1589 runs/s, 1869.1589 assertions/s.
1 runs, 1 assertions, 1 failures, 0 errors, 0 skips
```

Structuring Tests

Earlier we asked you to ignore the scaffolding around our tests. Now it's time to look at it.

You include the testing framework facilities in your unit by including minitest/autorun.

```
require "minitest/autorun"
```

The minitest/autorun module includes minitest itself, which is most of the features we've talked about so far. It also includes an alternate minitest/spec syntax that is more like RSpec we're not going to talk about in this book (if you want that style of syntax, we recommend actually using RSpec), and the minitest/mock mock object package. Finally, it calls Minitest.autorun, which