```
$ ruby -s prog -opt=electric ./mydata
```

-v, --verbose
: Sets $VERBOSE to true, which enables verbose mode. Also prints the version number. In verbose mode, compilation warnings are printed. If no program filename appears on the command line, Ruby exits.

-w
: Enables warning mode, which is like verbose mode, except it reads program from standard input if no program files are present on the command line. We recommend running your Ruby programs with -w.

-W level
: Sets the level of warnings issued. With a *level* of two (or with no level specified), equivalent to -w—additional warnings are given. If *level* is 1, runs at the standard (default) warning level. With -W0, absolutely no warnings are given (including those issued using Object.warn).

-x [directory]
: Strips off text before #!ruby line and changes working directory to *directory* if given.

Other Options

--dump option...
: Tells Ruby to dump various items of internal state. options... is a comma or space separated list containing one or more of insns, insns_without_opt, parsetree, parsetree_with_comment, and yydebug. This is intended for Ruby core developers.

Features that Can Be Enabled or Disabled

All of these features can be explicitly enabled or disabled from the command line, using an option such as --enable=gems or --disable=did_you_mean.

did_you_mean
: When enabled, a NameError will also show the results of a search of the recieving object for similarly named messages that might have been the intended message. Helpful when you can't quite remember the name of the message you want. Enabled by default.

error_highlight
: When enabled, error messages will have arrows highlighting the exact part of the line where the error was triggered. Useful in tracking down errors in a long line of code that chains multiple method calls. Enabled by default.

frozen-string-literal
: When enabled, acts as if the magic comment # frozen_string_literal: true is placed at the front of all Ruby files. This comment causes all string literals to be implicitly frozen without freeze being called on them. Disabled by default.

gems
: Stops Ruby from automatically loading RubyGems from require. Enabled by default

mjit
: Enables the mjit compiler. Disabled by default.