```
  fork do
    puts "Start of child 2, term = #{ENV['TERM']}"
  end
  Process.wait
  puts "End of child 1, term = #{ENV['TERM']}"
end
Process.wait
puts "Back in parent, term = #{ENV['TERM']}"
```

produces:

```
In parent, term = xterm-256color
Start of child 1, term = xterm-256color
Start of child 2, term = ansi
End of child 1, term = ansi
Back in parent, term = xterm-256color
```

Setting an environment variable's value to nil removes the variable from the environment.

Where Ruby Finds Its Libraries

You use require to bring a library into your Ruby program. Some of these libraries are supplied with Ruby, some may have been packaged as RubyGems, and some you may have written yourself. How does Ruby find them?

Let's start with the basics. When Ruby is built for your particular machine, it predefines a set of standard directories to hold library stuff. Where these are depends on the machine in question. You can determine this from the command line with something like this:

```
$ ruby -e 'puts $LOAD_PATH'
```

On our MacOs box, with rbenv installed, this produces the following list:

```
/opt/homebrew/Cellar/rbenv/1.2.0/rbenv.d/exec/gem-rehash
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/site_ruby/3.2.0
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/site_ruby/3.2.0/arm64-darwin22
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/site_ruby
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/vendor_ruby/3.2.0
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/vendor_ruby/3.2.0/arm64-darwin22
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/vendor_ruby
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/3.2.0
/Users/noel/.rbenv/versions/3.2.0/lib/ruby/3.2.0/arm64-darwin22
```

The site_ruby directories are intended to hold modules and extensions that you've added. The architecture-dependent directories (arm64-darwin21 in this case) hold executables and other things specific to this particular machine. All these directories are automatically included in Ruby's search for libraries.

Sometimes this isn't enough. Perhaps you're working on a large project written in Ruby and you and your colleagues have built a substantial library of Ruby code. You want everyone on the team to have access to all this code. And, for some reason, you don't want to package it as a Ruby Gem, you just want it to be in a known location in the file tree.

You have a couple of options to accomplish this. You can set the environment variable RUBYLIB to a list of one or more directories to be searched. (The separator between entries is a semicolon