Gem naming can be complicated, especially if the gem name is more than one word. There are a couple of different ways to find out.

If you go to the RubyGems website at rubygems.org, you will see a very prominently placed search feature. Typing "RSpec" into the search bar gives us a list of search results that tells us that, yes, rspec is the official name of the gem, and also that there are a lot of gems whose names start with rspec- (RSpec is split among several smaller gems, and there are also extensions to RSpec that use the same naming convention). Clicking on RSpec takes us to the RubyGems page for RSpec.

This page has a lot of useful information including the name of the gem, its self-description ("BDD for Ruby"), the current version (3.12.0, as this is written), a list of previous versions, and a list of the owners of the gem. The right column includes the number of times the gem has been downloaded, syntax for including the gem in a Gemfile or for installing from the command line (we'll get to that in a second), and links to a Homepage, a Source Code repo (often those two are the same thing), and a few other links that for most gems will all link back to the same GitHub page.

You can get some of this information from the command line:

```
$ gem search rspec -erd
rspec (3.12.0)
    Authors: Steven Baker, David Chelimsky, Myron Marston
    Homepage: http://github.com/rspec

    rspec-3.12.0
```

The gem search command searches the local and remote gem repositories for the text argument. The options used here are -e for "exact", searching for an exact match rather than a partial match (a partial match would give us a page or two of gems that contain the word "rspec"), -r for "remote only", and -d for details (otherwise we'd just get the names of the gems).

If we want to just list gems locally, the command is gem list. You can find a full description of all the gem command-line commands at https://guides.rubygems.org/command-reference.

Installing a Gem

After identifying the gem, the next step is it install it locally, which you can do with gem install:

```
$ gem install rspec
Successfully installed rspec-3.11.0
Parsing documentation for rspec-3.11.0
Installing ri documentation for rspec-3.11.0
Done installing documentation for rspec after 0 seconds
1 gem installed
```

The resulting text tells us that the most recent version of RSpec has been installed, as well as documentation for RSpec via the ri tool that we'll talk about in Chapter 19, Documenting Ruby, on page 315. If there are uninstalled dependent gems, those would also be installed at this time (the machine this is running on already has RSpec's dependencies installed).

What does it mean to install a gem? First off, the gem tool interacts with your current Ruby runtime to place the gem in a known location. We can find out where that is:

```
$ gem which rspec
```