This choice informs our decision on where to put the corresponding source files. Because class Options is inside the module Aaagnmr, it makes sense to put the corresponding file, options.rb, inside the lib/aaagnmr/ directory. This helps people who read your code in the future; when they see a name like A::B::C, they know to look for c.rb in the b/ directory in the a/ directory of your library. It also helps autoloaders find the file, when an autoloader sees a reference to Aaagnmr::Options, it knows that the corresponding file is lib/aaagnmr/options.rb.

Let's add the option parser. Its job is to take an array of command-line options and return to us the path to the dictionary file and the list of words to look up as anagrams. The source, in lib/aaagnmr/options.rb, looks like this:

gems/aaagmnr/lib/aaagmnr/options.rb

```
module Aaagmnr
  class Options
    DEFAULT_DICTIONARY = "/usr/share/dict/words"
    attr_reader :dictionary, :words_to_find

    def initialize(argv)
      @dictionary = DEFAULT_DICTIONARY
      parse(argv)
      @words_to_find = argv
    end

    private def parse(argv)
      OptionParser.new do |opts|
        opts.banner = "Usage:  anagram [ options ]  word..."

        opts.on("-d", "--dict path", String, "Path to dictionary") do |dict|
          @dictionary = dict
        end

        opts.on("-h", "--help", "Show this message") do
          puts opts
          exit
        end

        begin
          argv = ["-h"] if argv.empty?
          opts.parse!(argv)
        rescue OptionParser::ParseError => e
          warn e.message, "\n", opts
          exit(-1)
        end
      end
    end
  end
end
```

Notice how we define the Options class inside a top-level Aaagnmr module.

Let's write some unit tests. This should be fairly easy, because options.rb is self-contained—the only dependency is to the standard Ruby OptionParser (note that it's not explicitly required in this file because we've moved the require to the top-level aaagnmr.rb, which we'll show in a little bit. We're going to use RSpec here, because the gem library has already loaded it.

gems/aaagmnr/spec/aaagmnr/options_spec.rb

```
module Aaagmnr
  RSpec.describe Options do
```