```
    describe "without specifiying a dictionary" do
      it "returns the default dictionary" do
        opts = Options.new(["someword"])
        expect(opts.dictionary).to eq(Options::DEFAULT_DICTIONARY)
      end

      it "should retain specified words" do
        opts = Options.new(["word1", "word2"])
        expect(opts.words_to_find).to eq(["word1", "word2"])
      end
    end

    describe "when specifying a dictionary" do
      it "should be able to reference the specified dictionary" do
        opts = Options.new(["-d", "mydict", "someword"])
        expect(opts.dictionary).to eq("mydict")
      end

      it "should retain specified words" do
        opts = Options.new(["-d", "mydict", "word1", "word2"])
        expect(opts.words_to_find).to eq(["word1", "word2"])
      end
    end
  end
end
```

There are a few things to note in this file:

- You won't be able to run this without also updating the .gemspec file as shown below in Distributing and Installing Your Code, on page 272, the gem system will block you from running an incomplete .gemspec.
- We didn't need to require anything in this file, not our code, and not the option parser. That's because the RSpec spec_helper.rb requires our main file at lib/aagmnr.rb (we'll see this code in a moment), which does all of those things.
- We've put the RSpec file inside our module Aaagmnr, meaning that we can refer to our Options class directly rather than qualifying it as Aaagmnr::Options. Alternately, we could have started the file with RSpec.describe Aaagmnr::Options, but that has the potential to be flaky, we're now depending on the Aaagmnr module to already exist.

These tests pass, after you update the .gemspec file, you need to run them from the root directory of the gem:

```
$ rspec spec/aaagmnr/options_spec.rb
Aaagmnr::Options
  without specifiying a dictionary
    returns the default dictionary
    should retain specified words
  when specifying a dictionary
    should be able to reference the specified dictionary
    should retain specified words
Finished in 0.00099 seconds (files took 0.05874 seconds to load)
4 examples, 0 failures
```

The finder code (in lib/aaagmnr/finder.rb) is modified slightly from the original version. To make it easier to test, we'll have the default constructor take a list of words, rather than a