```
    end
  end
end
```

```
$ rspec spec/aaagmnr/finder_spec.rb
Aaagmnr::Finder
  signature
    is expected to eq "act"
    is expected to eq "act"
    is expected to eq "abmotw"
  lookup
    returns the word if the word is given
    returns the word if an anagram is given
    returns nil if no word matches the anagram
Finished in 0.00242 seconds (files took 0.05338 seconds to load)
6 examples, 0 failures
```

We now have all the support code in place. We just need to run it. We'll make the command-line interface—the thing the end user actually executes—really thin. It's in the exe/ directory in a file called aaagmnr (no rbextension, because that would be unusual in a command). (If you're on Windows, you might want to wrap the invocation of this in a cmd file.

gems/aaagmnr/exe/aaagmnr

```
#!/usr/bin/env ruby
require_relative "../lib/aaagmnr"

runner = Aaagmnr::Runner.new(ARGV)
runner.run
```

The code that this script invokes (lib/anagram/runner.rb) knits our other libraries together:

gems/aaagmnr/lib/aaagmnr/runner.rb

```
module Aaagmnr
  class Runner
    def initialize(argv)
      @options = Options.new(argv)
    end

    def run
      finder = Finder.from_file(@options.dictionary)
      @options.words_to_find.each do |word|
        anagrams = finder.lookup(word)
        if anagrams
          puts "Anagrams of #{word}: #{anagrams.join(", ")}"
        else
          puts "No anagrams of #{word} in #{@options.dictionary}"
        end
      end
    end
  end
end
```

With all our classes created, we can finally see the entire top-level file that is required by users of this gem:

gems/aaagmnr/lib/aaagmnr.rb

```
# frozen_string_literal: true
```