```
require_relative "aaagmnr/finder"
require_relative "aaagmnr/options"
require_relative "aaagmnr/runner"
require_relative "aaagmnr/version"
require "optparse"

module Aaagmnr
  class Error < StandardError; end
  # Your code goes here...
end
```

It requires all our files and the version, plus `optparse` – the custom error is created by the gem boilerplate, we don't really have any reason to use it yet.

Now that all our files are in place, we can run our program from the command line (use `chmod` to make the program executable).

```
$ exe/aaagmnr teaching ruby
Anagrams of teaching: cheating, teaching
Anagrams of ruby: bury, ruby
```

Distributing and Installing Your Code

There are a few parts of using RubyGems we haven't discussed. We haven't discussed the metadata that allows the RubyGems ecosystem to know things about our gem. In particular, we want to see how we can inject executables into code that uses our gem, and also how our gem declares its dependencies.

RubyGems needs to know information about your project that isn't contained in the directory structure. Instead, you have to write a short RubyGems specification. Our gem creation tool has already created one with most of the boilerplate at `aaagmnr.gemspec`. This comes with some lines marked `TODO` which must be changed before the gem can be used. Here's the completed file:

gems/aaagmnr/aaagmnr.gemspec

```
# frozen_string_literal: true

require_relative "lib/aaagmnr/version"

Gem::Specification.new do |spec|
  spec.name = "aaagmnr"
  spec.version = Aaagmnr::VERSION
  spec.authors = ["Noel Rappin"]
  spec.email = ["noel.rappin@pragprog.com"]

  spec.summary = "A simple anagrams tool"
  spec.homepage = "http://pragprog.com"
  spec.license = "MIT"
  spec.required_ruby_version = ">= 2.6.0"

  spec.metadata["homepage_uri"] = spec.homepage
  spec.metadata["source_code_uri"] = "http://pragprog.com"
  spec.metadata["changelog_uri"] = "http://pragprog.com"

  # Specify which files should be added to the gem when it is released.
  # The `git ls-files -z` loads the files in the RubyGem that have been added
  # into git.
  spec.files = Dir.chdir(File.expand_path(__dir__)) do
```