```
    `git ls-files -z`.split("\x0").reject do |f|
      (f == __FILE__) ||
        f.match(%r{\A(?:(?:test|spec|features)/|\.(?:git|travis|circleci)|appveyor)})
    end
  end
  spec.bindir = "exe"
  spec.executables = spec.files.grep(%r{\Aexe/}) { |f| File.basename(f) }
  spec.require_paths = ["lib"]

  spec.add_dependency "date_by_example", '~> 0.1'
end
```

The specification itself happens inside that Gem::Specification.new block, where the spec argument is the specification object and we're setting all kinds of attributes on it. Most of these are basically what they claim to be and are used, among other things, to populate the gem's page on rubygems.org should we submit it there.

The first line of the spec gives our gem a name. This is important—it will be used as part of the package name, and it will appear as the name of the gem when installed. The convention is for gem names to be all lower case, and to use underscores to separate words, as in date_by_example but use a dash to mark an extension to another gem, as in rspec-mocks. The dash indicates a submodule in the structure of the code, the main file of rspec-mocks would be rspec/mocks.

We pull the version string from the file inside the gem itself. The version string is significant, because RubyGems will use it both for package naming and for dependency management. The required_ruby_version tells RubyGems what versions of Ruby the gem would be expected to run with.

Eventually we get to spec.files which lists all the files that we want to be distributed when the gem is downloaded. That boilerplate code basically says "everything in the git repository that isn't a test or part of source control or CI". You can choose to change that if you want, you just need a list of files.

The spec.executables line tells RubyGems where to look for command-line scripts to get mixed in to users of the gem. The default is to include all files in the exe directory (because bin is used for developer scripts).

Finally we've used add_dependency to include the date_by_example gem. This tells RubyGems that any user of this gem must also install date_by_example. The second argument is a version specifier using the same syntax as we used in Gemfile. If we wanted a dependency that was only used for development, we'd use add_dev_dependency, but in practice, development dependencies are just as often added to the Gemfile.

Speaking of Gemfile, here it is:

gems/aaagmnr/Gemfile

```
# frozen_string_literal: true

source "https://rubygems.org"

# Specify your gem's dependencies in aaagmnr.gemspec
gemspec
gem "rake", "~> 13.0"
gem "rspec", "~> 3.0"
gem "standard", "~> 1.3"
```