:BACK_TRACE_LIMIT / back_trace_limit
Displays *n* initial and *n* final lines of backtrace. The default is 16.

:EVAL_HISTORY / save_history
Stores the result of all ERB commands, you can use _ to retrieve this or _[line_no] to get a specific line's result. Default is nil

:IGNORE_EOF / ignore_eof
Specifies the behavior of an end of file received on input. If true, it will be ignored; otherwise, irb will quit. Default is false.

:IGNORE_SIGINT / ignore_sigint
If false, ^C (Ctrl+c) will quit irb. If true, ^C during input will cancel input and return to the top level; during execution, ^C will abort the current operation. Default is true.

:INSPECT_MODE / inspect_mode
Specifies how values will be displayed: true or nil means use inspect, false uses to_s. Default is nil.

:IRB_NAME / irb_name
The name of an irb session, defaults to irb.

:IRB_RC
Can be set to a proc object that will be called when an irb session (or subsession) is started. Default is nil.

prompt_c
The prompt for a continuing statement (for example, immediately after an if).

prompt_i
The standard, top-level prompt.

:PROMPT_MODE / prompt_mode
The style of prompt to display. The default is :DEFAULT

prompt_s
The prompt for a continuing string. (depends)

:PROMPT
See Configuring the Prompt, on page 288.

:SAVE_HISTORY / save_history
The number of commands to save between irb sessions. The default is nil.

:USE_AUTOCOMPLETE
If true or nil use the autocomplete feature. Default is true.

:USE_COLORIZE
If true or nil colorize irb output. Default is true.

:USE_LOADER / use_loader
Specifies whether irb's own file reader method is used with load/require. Default is false.

:USE_MULTILINE
If true or nil use multiline edit mode. Default is nil.

:USE_SINGLELINE
If true or nil use singleline edit mode. Default is nil.