:USE_TRACER / use_tracer
: If true, traces the execution of statements. Default is false.

Commands

At the irb prompt, you can enter any valid Ruby expression and see the results. You can also use any of the following commands to control the irb session: (For some inexplicable reason, many of these commands have up to nine different aliases. We don't bother to show all of them.)

help ClassName, string, or symbol
: Displays the ri help for the given thing.

exit, quit, irb_exit, irb_quit
: Quits this irb session or subsession. If you've used cb to change bindings (detailed in a moment), exits from this binding mode.

conf, context, irb_context
: Displays current configuration. Modifying the configuration is achieved by invoking methods of conf. The list in irb Configuration Options, on page 285 shows the available conf settings.

  For example, to set the default prompt you could use this:

```
irb(main):001:0> conf.prompt_i = "Yes, Master? "
=> "Yes, Master? "
Yes, Master? 1 + 2
```

cb, irb_change_binding ‹obj›
: Creates and enters a new binding (sometimes called a *workspace*) that has its own scope for local variables. If *obj* is given, it will be used as self in the new binding.

pushb obj, popb
: Pushes and pops the current binding.

bindings
: Lists the current bindings.

irb_cwws
: Prints the object that's the binding of the current workspace.

irb ‹obj›
: Starts an irb subsession. If *obj* is given, it will be used as self.

jobs, irb_jobs
: Lists irb subsessions.

fg n, irb_fg n
: Switches into the specified irb subsession. *n* may be any of the following: an irb subsession number, a thread ID, an irb object, or the object that was the value of *self* when a subsession was launched.

kill n, irb_kill n
: Kills an irb subsession. *n* may be any of the values as described for irb_fg.