which will be documented as follows:

```
fred() { |index, position| ... }
```

:yields: is an example of a documentation modifier. These appear immediately after the start of the document element they are modifying. Other modifiers include:

:nodoc: ‹ all ›
: :nodoc: Don't include this element in the documentation. For classes and modules, the methods, aliases, constants, and attributes directly within the affected class or module will also be omitted from the documentation. By default, though, modules and classes within that class or module will be documented. This is turned off by adding the *all* modifier. For example, in the following code, only class SM::Input will be documented:

```
module SM  #:nodoc:
  class Input
  end
end

module Markup #:nodoc: all
  class Output
  end
end
```

:doc:
: :doc: This forces a method or attribute to be documented even if it wouldn't otherwise be. This is useful if, for example, you want to include documentation of a particular private method.

:notnew:
: :notnew: This is applicable only to the initialize instance method. Normally RDoc assumes that the documentation and parameters for #initialize are actually for the corresponding class's new method and so fakes out a new method for the class. The :notnew: modifier stops this. Remember that #initialize is protected, so you won't see the documentation unless you use the -a command-line option.

Other Directives

Comment blocks can contain other directives:

:call-seq: lines...
: :call-seq: Text up to the next blank comment line is used as the calling sequence when generating documentation (overriding the parsing of the method parameter list). A line is considered blank even if it starts with #. For this one directive, the leading colon is optional.

:include: filename
: :include: This includes the contents of the named file at this point. The file will be searched for in the directories listed by the --include option or in the current directory by default. The contents of the file will be shifted to have the same indentation as the : at the start of the :include: directive.

:title: text
: :title: This sets the title for the document. It's equivalent to the --title command-line parameter. (The command-line parameter overrides any :title: directive in the source.)