```
puts CGI.escape("Nicholas Payton/Trumpet & Flugel Horn")
```

produces:

```
Nicholas+Payton%2FTrumpet+%26+Flugel+Horn
```

More frequently, you may want to escape HTML special characters:

web/escape_01.rb

```
require "cgi"
puts CGI.escapeHTML("a < 100 && b > 200")
```

produces:

```
a &lt; 100 &amp;&amp; b &gt; 200
```

To get really fancy, you can decide to escape only certain HTML elements within a string:

web/escape_02.rb

```
require "cgi"
puts CGI.escapeElement("<hr><a href='/mp3'>Click Here</a><br>", "A")
```

produces:

```
<hr>&lt;a href=&#39;/mp3&#39;&gt;Click Here&lt;/a&gt;<br>
```

Here only the <a...> element is escaped; other elements are left alone. Each of these methods has an un- version to restore the original string:

web/escape_03.rb

```
require "cgi"
puts CGI.unescapeHTML("a &lt; 100 &amp;&amp; b &gt; 200")
```

produces:

```
a < 100 && b > 200
```

Using CGI.rb to Generate HTML

CGI contains a huge number of methods that can be used to create HTML—one method per element. To enable these methods, you must create a CGI object by calling new and passing in the required version of HTML. In these examples, we'll use html5.

To make element nesting easier, these methods take their content as code blocks. The code blocks should return a String, which will be used as the content for the element.

```
require 'cgi'
cgi = CGI.new("html5")
cgi.out do
  cgi.html do
    cgi.head { cgi.title { "This Is a Test"} } +
    cgi.body do
      cgi.form do
        cgi.hr +
        cgi.h1 { "A Form: " } +
        cgi.textarea("get_text") +
        cgi.br +
        cgi.submit
      end
    end
  end
end
```