Now we've got multiple files, we've moved all the gem requirements out of inline and into a Gemfile:

web/sinatra_01/Gemfile
```
source "https://rubygems.org"
gem "rack", "~> 2.2"
gem "puma"
gem "sinatra", "> 3.0"
```

As this is being written, Sinatra does not support Rack 3.0, so we've needed to use the Gemfile to ensure that we are using the most recent 2.2.x version of Rack.

At this point, we can run `bundle install`, and the Puma gem is installed. Then, running `puma` from the command line, Puma will find the `config.ru` file and run the Sinatra app. Pointing the browser at `http://localhost:9292` will show that this works.

There's a lot more to Sinatra, please check out https://sinatrarb.com for way more info. And if Sinatra doesn't meet your needs, there are many other Ruby web frameworks that might.

Ruby in the Browser with Web Assembly

Web Assembly (Wasm) is a virtual machine runtime engine that runs in a web browser, allowing any Wasm-complient programming language to be used as a scripting language in that browser.

Ruby 3.2 adds support for Wasm as a compilation target of Ruby. You can see full instructions for creating your own Wasm build at https://github.com/ruby/ruby/blob/master/wasm/README.md, but in most cases you'll likely either pull in the Wasm build as a module in Node Package Manager (NPM) or point to a source for the Wasm build in your web page.

So, you can do this in an HTML file:

web/wasm.html
```
<html>
<script
  src="https://cdn.jsdelivr.net/npm/ruby-head-wasm-wasi@0.5.0/dist/browser.script.iife.js"
></script>
<script type="text/ruby">
  puts "Welcome To Ruby!"
</script>
</html>
```

The first script tag downloads the Wasm-compliant Ruby build from a known CDN location. This will take some time on first download at least, so it's probably not quite production-ready as we write this. The first `script` tag registers the Ruby build as the interpreter for Ruby scripts, so subsequent `text/ruby` scripts will be interpreted by Ruby and their output sent to the browser.

In this case, the subsequent script prints "Welcome to Ruby!" to the browser console.

You can do more complex things:

web/wasm_2.html
```
<html>
<head>
  <script
```